

14014-B - Rocathaan Filler GF-400 - Base

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: 14014-B - Rocathaan Filler GF-400 - Base

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Filler for repairing surfaces. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Prokol Protective Coatings Duizeldonksestraat 44

5705 CA Helmond - Noord-Brabant - Nederland

Phone: +31 (0) 85 78 200 20

sds@prokol.nl www.prokol.com

1.4 Emergency telephone number: +31 (0) 85 78 200 20 Mon - Fri 8am - 4.45pm

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Eye Irrit. 2: Eye irritation, Category 2, H319

Repr. 2: Reproductive toxicity, Category 2, H361

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Warning







Hazard statements:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Precautionary statements:

P201: Obtain special instructions before use.

P264: Wash thoroughly after use.

P273: Avoid release to the environment.

 ${\tt P280: Wear \ protective \ gloves/face \ protection/protective \ clothing/respiratory \ protection/protective \ footwear.}}$

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P391: Collect spillage.

P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively.

Supplementary information:

EUH208: Contains 3-aminopropyltriethoxysilane, 4-morpholinecarbaldehyde. May produce an allergic reaction. EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Substances that contribute to the classification

Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol

2.3 Other hazards:

Product does not meet PBT/vPvB criteria



14014-B - Rocathaan Filler GF-400 - Base

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Formulated polyamines

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

COTICO				
Identification		Chemical name/Classification		
CAS:	Non-applicable	Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol Eye Irrit. 2: H319; Repr. 2: H361 - Warning	10 - <25 %	
CAS:	68479-98-1	Diethylmethylbenzenediamine Acute Tox. 4: H302+H312; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Irrit. 2: H319; STOT RE 2: H373 - Warning	2.5 - <5 %	
CAS:	102-60-3	1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol Eye Irrit. 2: H319 - Warning	1 - <2.5 %	
CAS:	13463-67-7	Titanium dioxide (aerodynamic diameter ≤ 10 μm) Carc. 2: H351 - Warning	1 - <2.5 %	
CAS:	919-30-2	3-aminopropyltriethoxysilane Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317 - Danger	<1 %	
CAS:	4394-85-8	4-morpholinecarbaldehyde Skin Sens. 1B: H317 - Warning	<1 %	

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acı	ute toxicity	Genus
Diethylmethylbenzenediamine	LD50 oral	598 mg/kg	Rat
CAS: 68479-98-1	LD50 dermal	1100 mg/kg	Rat
	LC50 inhalation	Not relevant	
3-aminopropyltriethoxysilane	LD50 oral	1491 mg/kg	Rat
CAS: 919-30-2	LD50 dermal	Not relevant	
	LC50 inhalation	Not relevant	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:



14014-B - Rocathaan Filler GF-400 - Base

SECTION 4: FIRST AID MEASURES (continued)

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...).

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

Date of compilation: 23/05/2024 Version: 1 Page 3/14



14014-B - Rocathaan Filler GF-400 - Base

SECTION 7: HANDLING AND STORAGE (continued)

A.-General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.-Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.-Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.-Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.-Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.-General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

errio, 2005 Workplace exposure mines, roaren eardon, pasionea 20201			
Identification	Occupational exposure limits		
Titanium dioxide (aerodynamic diameter ≤ 10 μm)	WEL (8h)		4 mg/m ³
CAS: 13463-67-7	WEL (15 min)		

DNEL (Workers):

		Short 6	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Reaction mass of 2-ethylpropane-1,3-diol and 5- ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: Non-applicable	Dermal	Not relevant	Not relevant	4.2 mg/kg	Not relevant
EC: 904-153-2	Inhalation	Not relevant	Not relevant	14.6 mg/m ³	Not relevant
Diethylmethylbenzenediamine	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 68479-98-1	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 270-877-4	Inhalation	Not relevant	Not relevant	0.13 mg/m ³	Not relevant
1,1´,1´´,1´´´-ethylenedinitrilotetrapropan-2-ol	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 102-60-3	Dermal	Not relevant	Not relevant	4.2 mg/kg	Not relevant
EC: 203-041-4	Inhalation	Not relevant	Not relevant	29.4 mg/m ³	Not relevant

Date of compilation: 23/05/2024 Version: 1 Page 4/14



14014-B - Rocathaan Filler GF-400 - Base

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short	exposure	Long 6	exposure
Identification		Systemic	Local	Systemic	Local
3-aminopropyltriethoxysilane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 919-30-2	Dermal	Not relevant	Not relevant	2 mg/kg	Not relevant
EC: 213-048-4	Inhalation	Not relevant	Not relevant	14 mg/m³	Not relevant
4-morpholinecarbaldehyde	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 4394-85-8	Dermal	Not relevant	Not relevant	11.7 mg/kg	Not relevant
EC: 224-518-3	Inhalation	Not relevant	Not relevant	50.3 mg/m ³	13.3 mg/m ³

DNEL (General population):

		Short e	exposure	Long e	exposure
Identification		Systemic	Local	Systemic	Local
Reaction mass of 2-ethylpropane-1,3-diol and 5- ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol	Oral	Not relevant	Not relevant	2.5 mg/kg	Not relevant
CAS: Non-applicable	Dermal	Not relevant	Not relevant	2.5 mg/kg	Not relevant
EC: 904-153-2	Inhalation	Not relevant	Not relevant	4.4 mg/m ³	Not relevant
Diethylmethylbenzenediamine	Oral	Not relevant	Not relevant	0.1 mg/kg	Not relevant
CAS: 68479-98-1	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 270-877-4	Inhalation	Not relevant	Not relevant	0.1 mg/m ³	Not relevant
1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol	Oral	Not relevant	Not relevant	2.5 mg/kg	Not relevant
CAS: 102-60-3	Dermal	Not relevant	Not relevant	2.5 mg/kg	Not relevant
EC: 203-041-4	Inhalation	Not relevant	Not relevant	8.7 mg/m ³	Not relevant
3-aminopropyltriethoxysilane	Oral	Not relevant	Not relevant	1 mg/kg	Not relevant
CAS: 919-30-2	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
EC: 213-048-4	Inhalation	Not relevant	Not relevant	3.5 mg/m ³	Not relevant
4-morpholinecarbaldehyde	Oral	Not relevant	Not relevant	4.17 mg/kg	Not relevant
CAS: 4394-85-8	Dermal	Not relevant	Not relevant	4.17 mg/kg	Not relevant
EC: 224-518-3	Inhalation	Not relevant	Not relevant	8.93 mg/m ³	13.3 mg/m ³

PNEC:

Identification				
Reaction mass of 2-ethylpropane-1,3-diol and 5- ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol	STP	100 mg/L	Fresh water	0.743 mg/L
CAS: Non-applicable	Soil	Not relevant	Marine water	0.074 mg/L
EC: 904-153-2	Intermittent	7.43 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant
Diethylmethylbenzenediamine	STP	17 mg/L	Fresh water	0.001 mg/L
CAS: 68479-98-1	Soil	0.0056 mg/kg	Marine water	0 mg/L
EC: 270-877-4	Intermittent	0.005 mg/L	Sediment (Fresh water)	0.029 mg/kg
	Oral	0.002 g/kg	Sediment (Marine water)	0.003 mg/kg
1,1´,1´´,1´´´-ethylenedinitrilotetrapropan-2-ol	STP	70 mg/L	Fresh water	0.085 mg/L
CAS: 102-60-3	Soil	0.018 mg/kg	Marine water	0.009 mg/L
EC: 203-041-4	Intermittent	1.51 mg/L	Sediment (Fresh water)	0.193 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.019 mg/kg
3-aminopropyltriethoxysilane	STP	1.3 mg/L	Fresh water	Not relevant
CAS: 919-30-2	Soil	Not relevant	Marine water	Not relevant
EC: 213-048-4	Intermittent	Not relevant	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant
4-morpholinecarbaldehyde	STP	2000 mg/L	Fresh water	0.5 mg/L
CAS: 4394-85-8	Soil	0.244 mg/kg	Marine water	0.05 mg/L
EC: 224-518-3	Intermittent	5 mg/L	Sediment (Fresh water)	2.69 mg/kg
	Oral	Not relevant	Sediment (Marine water)	0.269 mg/kg

8.2 Exposure controls:

A.-Individual protection measures, such as personal protective equipment

Date of compilation: 23/05/2024 Version: 1 Page 5/14



14014-B - Rocathaan Filler GF-400 - Base

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.-Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.-Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	NON-disposable chemical protective gloves	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.-Eye and face protection

Pictogram	PPE	Remarks
Mandatory face	Face shield	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
*	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	**	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012:

V.O.C. (Supply): 1.8 % weight

V.O.C. density at 20 °C: 20.11 kg/m³ (20.11 g/L)



14014-B - Rocathaan Filler GF-400 - Base

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liauid

Appearance: Characteristic Colour: Characteristic Odour: Characteristic Odour threshold: Not relevant *

Volatility:

58 - 358 °C Boiling point at atmospheric pressure:

Vapour pressure at 20 °C: 56 Pa

Vapour pressure at 50 °C: 423.74 Pa (0.42 kPa)

Evaporation rate at 20 °C: Not relevant *

Product description:

Density at 20 °C: 1117 kg/m³ Relative density at 20 °C: 1.117

Dynamic viscosity at 20 °C: Not relevant * Kinematic viscosity at 20 °C: Not relevant * Kinematic viscosity at 40 °C: Not relevant * Concentration: Not relevant * pH: Not relevant * Vapour density at 20 °C: Not relevant * Partition coefficient n-octanol/water 20 °C: Not relevant * Solubility in water at 20 °C: Not relevant * Solubility properties: Not relevant * Decomposition temperature: Not relevant *

Melting point/freezing point: Not relevant *

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Not relevant *

275 °C Autoignition temperature:

Lower flammability limit: Not relevant * Upper flammability limit: Not relevant *

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties: Not relevant * Oxidising properties: Not relevant * Corrosive to metals: Not relevant * Heat of combustion: Not relevant * Aerosols-total percentage (by mass) of Not relevant *

flammable components: Other safety characteristics:

Surface tension at 20 °C: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

Date of compilation: 23/05/2024 Version: 1 Page 7/14



14014-B - Rocathaan Filler GF-400 - Base

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Refraction index: Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Not applicable	Not applicable	Not applicable	Not applicable	Not applicable	
Shock and friction	Contact with air	Increase in temperature Sunlight		Humidity	

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Precaution	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO_2) , carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):



14014-B - Rocathaan Filler GF-400 - Base

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3. IARC: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (3); Zeolites (3); phenol (3); Titanium dioxide (aerodynamic diameter ≤ 10 µm) (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Suspected of damaging fertility or the unborn child

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

CAS 13463-67-7 Titanium dioxide (aerodynamic diameter $\leq 10~\mu m$): The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10~\mu m$

Specific toxicology information on the substances:

Identification		ite toxicity	Genus
Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol	LD50 oral	>5000 mg/kg	
CAS: Non-applicable	LD50 dermal	>10000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
Diethylmethylbenzenediamine	LD50 oral	598 mg/kg (ATEi)	Rat
CAS: 68479-98-1	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	>20 mg/L	
1,1´,1´´,1´´´-ethylenedinitrilotetrapropan-2-ol	LD50 oral	>5000 mg/kg	
CAS: 102-60-3	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Titanium dioxide (aerodynamic diameter ≤ 10 µm)	LD50 oral	10000 mg/kg	Rat
CAS: 13463-67-7	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	
3-aminopropyltriethoxysilane	LD50 oral	1491 mg/kg	Rat
CAS: 919-30-2	LD50 dermal	4000 mg/kg	Rabbit
	LC50 inhalation	>20 mg/L	
4-morpholinecarbaldehyde	LD50 oral	7475 mg/kg	Rat
CAS: 4394-85-8	LD50 dermal	18400 mg/kg	Rabbit
	LC50 inhalation	>5 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available Toxic to aquatic life with long lasting effects.

Date of compilation: 23/05/2024 Version: 1 Page 9/14



14014-B - Rocathaan Filler GF-400 - Base

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.1 Toxicity:

Acute toxicity:

reace toxicity.				
Identification		Concentration	Species	Genus
Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl- 1,3-dioxane-5-methanol and propylidynetrimethanol	LC50	>10000 mg/L (96 h)	N/A	Fish
CAS: Non-applicable	EC50 >100 mg/L (48 h)		Daphnia sp.	Crustacean
	EC50	>100 mg/L (72 h)	N/A	Algae
Diethylmethylbenzenediamine	LC50	194 mg/L (48 h)	Leuciscus idus	Fish
CAS: 68479-98-1	EC50	0.5 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Not relevant		
1,1´,1´´,1´´´-ethylenedinitrilotetrapropan-2-ol	LC50	4600 mg/L (96 h)	Leuciscus idus	Fish
CAS: 102-60-3		Not relevant		
	EC50	150 mg/L (72 h)	Desmodesmus subspicatus	Algae
3-aminopropyltriethoxysilane	LC50	934 mg/L (96 h)	Danio rerio	Fish
CAS: 919-30-2	EC50	331 mg/L (48 h)	N/A	Crustacean
	EC50	603 mg/L (72 h)	Desmodesmus subspicatus	Algae
4-morpholinecarbaldehyde	LC50	500 mg/L (96 h)	Leuciscus idus	Fish
CAS: 4394-85-8	EC50	Not relevant		
	EC50	23880 mg/L (72 h)	Desmodesmus subspicatus	Algae

Chronic toxicity:

Identification		Concentration	Species	Genus
1,1',1'',1'''-ethylenedinitrilotetrapropan-2-ol CAS: 102-60-3		Not relevant		
		10 mg/L	Daphnia magna	Crustacean
4-morpholinecarbaldehyde	NOEC	1 mg/L	N/A	Fish
CAS: 4394-85-8		1 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degr	adability	Biodegrada	bility
Reaction mass of 2-ethylpropane-1,3-diol and 5- ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol	BOD5	Not relevant	Concentration	Not relevant
CAS: Non-applicable	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	84 %
1,1´,1´´,1´´´-ethylenedinitrilotetrapropan-2-ol	BOD5	Not relevant	Concentration	107 mg/L
CAS: 102-60-3	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	36 %
3-aminopropyltriethoxysilane	BOD5	Not relevant	Concentration	Not relevant
CAS: 919-30-2	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	67 %
4-morpholinecarbaldehyde	BOD5	Not relevant	Concentration	100 mg/L
CAS: 4394-85-8	COD	Not relevant	Period	30 days
	BOD5/COD	Not relevant	% Biodegradable	100 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccum	nulation potential
Reaction mass of 2-ethylpropane-1,3-diol and 5-ethyl-1,3-dioxane-5-methanol and propylidynetrimethanol	BCF	
CAS: Non-applicable	Pow Log	8
	Potential	
4-morpholinecarbaldehyde	BCF	1
CAS: 4394-85-8	Pow Log	-1.2
	Potential	Low

12.4 Mobility in soil:

Date of compilation: 23/05/2024 Version: 1 Page 10/14



14014-B - Rocathaan Filler GF-400 - Base

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Identification Absorption/desorption		Volatility	
4-morpholinecarbaldehyde	Кос	1		2.302E-3 Pa·m³/mol
CAS: 4394-85-8	Conclusion	Very High	Dry soil	No
	Surface tension	Not relevant	Moist soil	No

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste:

HP14 Ecotoxic, HP10 Toxic for reproduction

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:



14.1 UN number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Diethylmethylbenzenediamine)

Page 11/14

14.3 Transport hazard class

(es): Labels:

9

14.4 Packing group: III **14.5 Environmental hazards:** Yes

14.6 Special precautions for user

Tunnel restriction code: -

Physico-Chemical properties: see section 9

Limited quantities: 5 L

14.7 Transport in bulk Not relevant

according to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 41-22:

- CONTINUED ON NEXT PAGE -



14014-B - Rocathaan Filler GF-400 - Base

SECTION 14: TRANSPORT INFORMATION (continued)

14.1 UN number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Diethylmethylbenzenediamine)

14.3 Transport hazard class

(es):

Labels: 9
14.4 Packing group: III
14.5 Marine pollutant: Yes
14.6 Special precautions for user

Special regulations: 335, 969, 274
EmS Codes: F-A, S-F
Physico-Chemical properties: see section 9

Limited quantities: 5 L

Segregation group: Not relevant **14.7 Transport in bulk** Not relevant

according to Annex II of Marpol and the IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:



14.1 UN number: UN3082

14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,

N.O.S. (Diethylmethylbenzenediamine)

14.3 Transport hazard class

(es):

Labels: 9
14.4 Packing group: III
14.5 Environmental hazards: Yes
14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Transport in bulk** Not relevant

according to Annex II of Marpol and the IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): Not relevant
- Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

The Control of Major Accident Hazards Regulations 2015:

Section	Description	Lower-tier requirements	Upper-tier requirements
E2	ENVIRONMENTAL HAZARDS	200	500

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects. Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Specific provisions in terms of protecting people or the environment:



14014-B - Rocathaan Filler GF-400 - Base

SECTION 15: REGULATORY INFORMATION (continued)

It is recommended to use the information included in this safety data sheet as a basis for conducting workplacespecific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.

H361: Suspected of damaging fertility or the unborn child.

H411: Toxic to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Acute Tox. 4: H302 - Harmful if swallowed.

Acute Tox. 4: H302+H312 - Harmful if swallowed or in contact with skin.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Carc. 2: H351 - Suspected of causing cancer (Inhalation).

Eye Irrit. 2: H319 - Causes serious eye irritation.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1B: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

Classification procedure:

Eye Irrit. 2: Calculation method Repr. 2: Calculation method

Aquatic Chronic 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer



14014-B - Rocathaan Filler GF-400 - Base

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -

Date of compilation: 23/05/2024 Version: 1 Page 14/14