


42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** 42081-H - Prokol FireGuard Pro 200 - Harder
Other means of identification:
Not relevant
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Hardener for coatings. For professional users only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Prokol Protective Coatings
Duizeltonksestraat 44
5705 CA Helmond - Noord-Brabant - Nederland
Phone: +31 (0) 85 78 200 20
sds@prokol.nl
www.prokol.com
- 1.4 Emergency telephone number:** +31 (0) 85 78 200 20 Mon - Fri 8am - 4.45pm

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Acute Tox. 4: Acute inhalation toxicity, Category 4, H332
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Warning
- 
- Hazard statements:**
Acute Tox. 4: H332 - Harmful if inhaled.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT SE 3: H335 - May cause respiratory irritation.
- Precautionary statements:**
P261: Avoid breathing vapours
P271: Use only outdoors or in a well-ventilated area.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear.
P302+P352: IF ON SKIN: Wash with plenty of water.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
- Supplementary information:**
EUH204: Contains isocyanates. May produce an allergic reaction.
- Substances that contribute to the classification**
Hexamethylene diisocyanate, oligomers
- Additional Labelling:**
As from 24 August 2023 adequate training is required before industrial or professional use.
UFI: 80N0-Q0DD-6008-T1W8

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 2: HAZARDS IDENTIFICATION (continued)

2.3 Other hazards:

Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:





Non-applicable

3.2 Mixture:

Chemical description: Isocyanate resin

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|--|---|-----------------------|
| CAS: 28182-81-2 EC: 931-274-8 Index: Non-applicable REACH:01-2119485796-17-XXXX | Hexamethylene diisocyanate, oligomers⁽¹⁾ Self-classified | 75 - <100 % |
| | Regulation 1272/2008 Acute Tox. 4: H332; Skin Sens. 1: H317; STOT SE 3: H335 - Warning  | |
| CAS: 25640-78-2 EC: 247-156-8 Index: Non-applicable REACH:01-2119982993-17-XXXX | (1-methylethyl)-1,1'-biphenyl⁽¹⁾ Self-classified | 2.5 - <5 % |
| | Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Eye Irrit. 2: H319 - Danger    | |

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

| Identification | Acute toxicity | | Genus |
|---------------------------------------|----------------|----------------|-------|
| | LD50 oral | LD50 dermal | |
| Hexamethylene diisocyanate, oligomers | Not relevant | Not relevant | |
| CAS: 28182-81-2 | Not relevant | 11 mg/L (ATEi) | |
| EC: 931-274-8 | | | |

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

May cause an allergic skin reaction. In case of contact it is recommended to clean the affected area thoroughly with water and neutral soap. In case of changes on the skin (stinging, redness, rashes, blisters, ...), seek medical advice with this Safety Data Sheet

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder**SECTION 4: FIRST AID MEASURES (continued)**

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media:****Suitable extinguishing media:**

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures:****For non-emergency personnel:**

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling:**

A.-General precautions for safe use

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 7: HANDLING AND STORAGE (continued)

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C
Maximum Temp.: 30 °C
Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|---|------------|----------------|---------------------|------------------------|-----------------------|
| | | Systemic | Local | Systemic | Local |
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | Not relevant | Not relevant |
| | Inhalation | Not relevant | 1 mg/m ³ | Not relevant | 0.5 mg/m ³ |
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | Oral | Not relevant | Not relevant | Not relevant | Not relevant |
| | Dermal | Not relevant | Not relevant | 2 mg/kg | Not relevant |
| | Inhalation | Not relevant | Not relevant | 7.05 mg/m ³ | Not relevant |

DNEL (General population):

Not relevant

PNEC:

| Identification | | Short exposure | | Long exposure | |
|---|--------------|----------------|-------------------------|---------------|-------|
| | | Systemic | Local | Systemic | Local |
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | STP | 88 mg/L | Fresh water | 0.127 mg/L | |
| | Soil | 53183 mg/kg | Marine water | 0.013 mg/L | |
| | Intermittent | 1.27 mg/L | Sediment (Fresh water) | 266701 mg/kg | |
| | Oral | Not relevant | Sediment (Marine water) | 26670 mg/kg | |
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | STP | 2 mg/L | Fresh water | 0.00054 mg/L | |
| | Soil | 0.2699 mg/kg | Marine water | 0.000054 mg/L | |
| | Intermittent | 0.003 mg/L | Sediment (Fresh water) | 1.355 mg/kg | |
| | Oral | Not relevant | Sediment (Marine water) | 0.1355 mg/kg | |

8.2 Exposure controls:

- CONTINUED ON NEXT PAGE -


42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|---|-----------------------------------|---|---------------------|--|
|  Mandatory respiratory tract protection | Filter mask for gases and vapours |  | EN 405:2002+A1:2010 | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands



| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---------------------------------------|---|--------------|--|
|  Mandatory hand protection | Protective gloves against minor risks |  | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN ISO 21420:2020 and EN ISO 374-1:2016+A1:2018 |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|---------------------------------|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2002 EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|----------------------|---|-------------------|---|
| | Work clothing |  | | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
| | Anti-slip work shoes |  | EN ISO 20347:2022 | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2022 y EN 13832-1:2007 |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0 % weight

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| | |
|---------------------------|-----------------------------|
| V.O.C. density at 20 °C: | 0 kg/m ³ (0 g/L) |
| Average carbon number: | Not relevant |
| Average molecular weight: | Not relevant |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

| | |
|--------------------------|----------------|
| Physical state at 20 °C: | Liquid |
| Appearance: | Characteristic |
| Colour: | Characteristic |
| Odour: | Characteristic |
| Odour threshold: | Not relevant * |

Volatility:

| | |
|--|-----------------|
| Boiling point at atmospheric pressure: | 192 - 396 °C |
| Vapour pressure at 20 °C: | 6.069E-2 Pa |
| Vapour pressure at 50 °C: | 1.43 Pa (0 kPa) |
| Evaporation rate at 20 °C: | Not relevant * |

Product description:

| | |
|--|----------------------------|
| Density at 20 °C: | 1121.4 kg/m ³ |
| Relative density at 20 °C: | 1.121 |
| Dynamic viscosity at 20 °C: | 3000 cP |
| Kinematic viscosity at 20 °C: | 2675.27 mm ² /s |
| Kinematic viscosity at 40 °C: | Not relevant * |
| Concentration: | Not relevant * |
| pH: | Not relevant * |
| Vapour density at 20 °C: | Not relevant * |
| Partition coefficient n-octanol/water 20 °C: | Not relevant * |
| Solubility in water at 20 °C: | Not relevant * |
| Solubility properties: | Not relevant * |
| Decomposition temperature: | Not relevant * |
| Melting point/freezing point: | Not relevant * |

Flammability:

| | |
|----------------------------|------------------------|
| Flash Point: | Non Flammable (>60 °C) |
| Flammability (solid, gas): | Not relevant * |
| Autoignition temperature: | 430 °C |
| Lower flammability limit: | Not relevant * |
| Upper flammability limit: | Not relevant * |

Particle characteristics:

| | |
|-----------------------------|----------------|
| Median equivalent diameter: | Non-applicable |
|-----------------------------|----------------|

9.2 Other information:

Information with regard to physical hazard classes:

| | |
|-----------------------|----------------|
| Explosive properties: | Not relevant * |
| Oxidising properties: | Not relevant * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|--|----------------|
| Corrosive to metals: | Not relevant * |
| Heat of combustion: | Not relevant * |
| Aerosols-total percentage (by mass) of flammable components: | Not relevant * |
| Other safety characteristics: | |
| Surface tension at 20 °C: | Not relevant * |
| Refraction index: | Not relevant * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|----------------|----------------|
| Not applicable | Not applicable | Not applicable | Not applicable | Not applicable |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Not applicable | Not applicable | Avoid alkalis or strong bases |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Not relevant
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|---|-----------------|----------------|--------|
| | | | |
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | LD50 oral | 5100 mg/kg | Rat |
| | LD50 dermal | >2000 mg/kg | |
| | LC50 inhalation | 11 mg/L (ATEi) | |
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | LD50 oral | 4650 mg/kg | Rat |
| | LD50 dermal | >5000 mg/kg | Rabbit |
| | LC50 inhalation | >20 mg/L | |

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available
Harmful to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Concentration | | Species | Genus |
|---|---------------|------------------|-------------------------|------------|
| Hexamethylene diisocyanate, oligomers CAS: 28182-81-2 EC: 931-274-8 | LC50 | Not relevant | | |
| | EC50 | Not relevant | | |
| | EC50 | 1000 mg/L (72 h) | Scenedesmus subspicatus | Algae |
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | LC50 | 0.6 mg/L (96 h) | Oryzias latipes | Fish |
| | EC50 | 0.24 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | >100 mg/L (72 h) | Desmodesmus subspicatus | Algae |

Chronic toxicity:

| Identification | Concentration | | Species | Genus |
|--|---------------|--------------|---------------|------------|
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | NOEC | Not relevant | | |
| | NOEC | 0.028 mg/L | Daphnia magna | Crustacean |

12.2 Persistence and degradability:

Substance-specific information:

| Identification | Degradability | | Biodegradability | |
|---|---------------|--------------|------------------|------------|
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | BOD5 | Not relevant | Concentration | 19.65 mg/L |
| | COD | Not relevant | Period | 28 days |
| | BOD5/COD | Not relevant | % Biodegradable | 60 % |

12.3 Bioaccumulative potential:

Substance-specific information:

| Identification | Bioaccumulation potential | |
|---|---------------------------|-----------|
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | BCF | 2896 |
| | Pow Log | 5.33 |
| | Potential | Very High |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|---|-----------------------|--------------|------------|------------------------------|
| (1-methylethyl)-1,1'-biphenyl CAS: 25640-78-2 EC: 247-156-8 | Koc | 25055 | Henry | 173.3 Pa·m ³ /mol |
| | Conclusion | Immobile | Dry soil | Yes |
| | Surface tension | Not relevant | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | Hazardous |

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP13 Sensitising

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC, The Waste Regulations 2011, 2011 No. 988). As under 15 01 (2014/955/EU) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated
Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Not relevant

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

—ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

—tricks and jokes,

—games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains more than 0.1 % of Hexamethylene diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

— handling open mixtures at ambient temperature (including foam tunnels)

— spraying in a ventilated booth

— application by roller

— application by brush

— application by dipping and pouring

— mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore

— cleaning and waste

— any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

— handling incompletely cured articles (e.g. freshly cured, still warm)

— foundry applications

— maintenance and repair that needs access to equipment

— open handling of warm or hot formulations (> 45 °C)

— spraying in open air, with limited or only natural ventilation (includes large industry working halls) and

spraying with high energy (e.g. foams, elastomers)

— and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

— chemistry of diisocyanates

— toxicity hazards (including acute toxicity)

— exposure to diisocyanates

— occupational exposure limit values

— how sensitisation can develop

— odour as indication of hazard

— importance of volatility for risk

— viscosity, temperature, and molecular weight of diisocyanates

— personal hygiene

— personal protective equipment needed, including practical instructions for its correct use and its limitations

— risk of dermal contact and inhalation exposure

— risk in relation to application process used

— skin and inhalation protection scheme

— ventilation

— cleaning, leakages, maintenance

— discarding empty packaging

— protection of bystanders

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder

SECTION 15: REGULATORY INFORMATION (continued)

- identification of critical handling stages
 - specific national code systems (if applicable)
 - behaviour-based safety
 - certification or documented proof that training has been successfully completed
 - (b) intermediate level training, including on-line training, on:
 - additional behaviour-based aspects
 - maintenance
 - management of change
 - evaluation of existing safety instructions
 - risk in relation to application process used
 - certification or documented proof that training has been successfully completed
 - (c) advanced training, including on-line training, on:
 - any additional certification needed for the specific uses covered
 - spraying outside a spraying booth
 - open handling of hot or warm formulations (> 45 °C)
 - certification or documented proof that training has been successfully completed
6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.
7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.
8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.
9. Member States shall include in their reports pursuant to Article 117(1) the following information:
- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
 - (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
 - (c) national exposure limits for diisocyanates, if there are any
 - (d) information about enforcement activities related to this restriction.
10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (CDG 2009), SI 2009 No 1348
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment (Amendment) Regulations 2011, 2011 No. 1885
Control of Substances Hazardous to Health Regulations 2002 (as amended)
EH40/2005 Workplace exposure limits
The Waste Regulations 2011, 2011 No. 988

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.
H412: Harmful to aquatic life with long lasting effects.
H332: Harmful if inhaled.

- CONTINUED ON NEXT PAGE -

42081-H - Prokol FireGuard Pro 200 - Harder**SECTION 16: OTHER INFORMATION (continued)****Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Skin Sens. 1: Calculation method

STOT SE 3: Calculation method

Aquatic Chronic 3: Calculation method

Acute Tox. 4: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>

<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

LC50: Lethal Concentration 50

EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient

Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -